



BROTHER		<<unit in mm>>		
Description	S k e t c h	Machine Model No.	Hole Size	Wire Size
RBR-1C		HS-300	0.105 $^{+0.005}_0$	0.1
		HS-350	0.110 $^{+0.005}_0$	0.1
		(CONT series)	0.155 $^{+0.005}_0$	0.15
			0.205 $^{+0.005}_0$	0.2
			0.255 $^{+0.005}_0$	0.25
			0.260 $^{+0.005}_0$	0.25
			0.270 $^{+0.005}_0$	0.25
			0.305 $^{+0.005}_0$	0.3
	Common	055		
RBR-2U		HS-3100	0.110 $^{+0.003}_0$	0.1
		HS-3600	0.155 $^{+0.003}_0$	0.15
		HS-5100	0.210 $^{+0.003}_0$	0.2
		HS-50A	0.260 $^{+0.003}_0$	0.25
		(ATU GUIDE)	0.310 $^{+0.003}_0$	0.3
	Upper	124		
RBR-3L		HS-3100	0.110 $^{+0.003}_0$	0.1
		HS-3600	0.155 $^{+0.003}_0$	0.15
		HS-5100	0.210 $^{+0.003}_0$	0.2
		HS-50A	0.260 $^{+0.003}_0$	0.25
		(ATL GUIDE)	0.310 $^{+0.003}_0$	0.3
	Lower	125		
RBR-4C		HS-3100	0.110 $^{+0.003}_0$	0.1
		HS-3600	0.160 $^{+0.003}_0$	0.15
		HS-5100	0.205 $^{+0.003}_0$	0.2
		(STD GUIDE)	0.255 $^{+0.003}_0$	0.25
			0.305 $^{+0.003}_0$	0.3
	Common	145		